



## EASY FLOOR

### MATT COLOURLESS WATER\_BASED PAINT FOR FLOORS AND WALLS

#### Description

EASY FLOOR is a single-component water-based matt paint for the protection and decoration of indoor and outdoor floors and walls. The polymer content gives excellent resistance to light, to abrasion and to bad weather conditions in general. Suitable for concrete floors, it offers a pleasant matt appearance in both residential and commercial buildings.

#### Characteristics

The product is suitable for painting in areas where food is stored, in particular for walls and ceilings that require good resistance to frequent washing. It can be washed with an alkaline de-greasing detergent (detergent B). The product has a very low level of dirt retention.

#### Composition

EASY FLOOR : water-based pure acrylic polymer, cellulose, wetting and dispersing agents, natural preservatives.

#### Surfaces

EASY FLOOR should be applied on clean, dry and smooth surfaces, exempt of salt deposits and humidity and without traces of oils or fatty substances. No pre-treatment is necessary on new surfaces, on already painted or deteriorated surfaces, it is necessary to remove the existing paint and dust or brush the surface clean.

It is advisable to carry out a preliminary test before application.

#### Preparation of the mix

Stir well before use. The product is ready to use, but can be diluted to a maximum of 5% water for the first coat to facilitate penetration into the surface.

EASY FLOOR is colourless but can be coloured with all of our natural pigments and with the tintometric **Color Grain** or **Imagine system**.

The recommended quantity of colorant is maximum 5% with regard to the weight of the product.

#### Application

Apply one or two coats by brush, short-haired roller, or spray.

The product will dry on the surface in about 1-2 hours and in depth in 24 hours. We recommend that the second coat be applied 6 - 8 hours after the first coat.

Do not apply with temperatures below +15°C or superior to +35°C.

The "Wet look" increases with the number of coats applied. Wash equipment with water after use.

#### Warning

Protect doors, windows, curtains and all parts that should not be painted. Any stains or splashes should be immediately removed with water.

#### Consumption

The optimum quantity can be determined by carrying out a preliminary test on a small area.

The yield depends on the absorption of the surface to be treated : indicatively one can expect consumption of between 9 & 11sqm. /l

#### Equipment for application

Application systems: brush, spray, immersion. Transfer efficiency : 30-45% with air-brush ; 90-95% by immersion, 90-95% by brush.

#### Packaging and storage

Plastic cans of 5 l and 25 l.

Specific weight kg 1.040 x l

EASY FLOOR should be stored in a fresh and dry place, in the original containers, which should be well-sealed. It is stable for at least twelve months providing the temperature does not drop to below +5°C or rise to more than +30°C.

#### Health and safety regulations

Ventilate during application. Avoid contact with the skin and eyes. In the case of contact, wash immediately and abundantly with water.

Keep out of the reach of children.

For further information see the safety sheet.

#### Disposal

Dispose of the product according to local regulations. Containers must be re-cycled.

#### Classification UE

Directive n. 2004/42 CE :

Category A/e Liquid phase : limit of VOC : 130 g/l

VOC Volatile organic compounds = 38,6 g/l

27/03/19

The advice and indications given above are based on our experience and are of an informative nature only and do not bind us to any responsibility. The application of the products takes place without our direct control, the user therefore takes all responsibility for any consequences of use. Our technical assistance team is available for any further information that might be necessary.