

Technical data sheet PL/1150



FANCY ECO

Ecological paint for interiors. Breathable with low VOC content.



Description

FANCY ECO is a water and vinyl-acetate based emulsion for painting wall surfaces. It is particularly suitable for decorating and protecting internal wall surfaces.

Characteristics

FANCY ECO is breathable thanks to its particular formula which is exempt from glycols and dangerous substances. FANCY ECO gives a pleasant matt finish to the surfaces on which it is applied as well as good resistance to dirt. It has a very strong white appearance and it has very good covering capacity. The product is formulated with top quality ingredients.

FANCY ECO is a paint with a low level of volatile organic compounds (VOC).

Composition

FANCY ECO : water, methyl cellulose, white titanium oxide, calcium carbonate, vinyl versate emulsion, moisturising agents, dispersers, about 0.1% preservatives.

Surfaces

FANCY ECO is applied on various types of surfaces such as cement-based plasters, mixed plasters, plaster, plaster-board, cement fibre and all already-painted surfaces. The product should be applied on dry surfaces, that are not flaky and are exempt of humidity and salts.

Preparation of surfaces

On new surfaces no pre-treatment is necessary. In any case we recommend a coat of primer **Isofree (IS/0245)** or **Isoacril (IS/0240)** diluted 1/7 - 1/8 with water, to create uniform absorption and reduce consumption ; on already painted or deteriorated surfaces it is necessary to eliminate the existing paint which presents problems of adhesion with the surface, fill any cracks with filler and apply a coat of ecological fixer **Isofree (IS/0245)** diluted 1/7 or 1/8 to re-aggregate and level the surface. After applying Isofree wait 6-8 hours before applying a first coat of FANCY ECO.

Application

Stir well before use.

This paint is usually diluted with about 20% - 30% of water, depending on the conditions of application, on the nature of the surface and the tools used for application.

Applied in two coats, the product is dry to the touch after 4 – 6 hours and in depth after 24 hours.

Do not apply in a temperature below +5°C or above +35°C or with a level of humidity >80%.

Colours

FANCY ECO breathable paint is white and thanks to the **Imagine, Elements, Ral, Ncs** colouring system, it is possible to obtain more than 1000 colours with our collection of universal colouring pastes which are non toxic and VOC exempt.

Warning

Protect doors, windows, frames and in general all parts that should not be painted. Any splashes or drips should be immediately removed with water.

Consumption

FANCY ECO has a yield of 9 - 11 m²/lt depending on absorption and the type of surface.

Equipment for application

FANCY ECO can be applied with brush, roller, or by spraying. Wash equipment with water after use.

Packaging and storage

Plastic buckets of 5 and 14 lt

FANCY ECO should be stored in the original containers, that are well-sealed and is stable for at least 12 months, providing it is kept in a room where the temperature is not below +5°C or above +30°C.

Health and safety regulations

Ventilate during application.

Avoid contact with the eyes and skin, in the case of contact wash immediately and abundantly with water.

Keep out of the reach of children. For the evaluation of information regarding toxic elements, please consult the health and safety sheet.

Disposal

Dispose of the product according to local health and safety regulations. Empty containers must be recycled.

Classification and technical characteristics

Directive n° 2004/42/CE Maximum content of VOC in paints and varnishes.

Category a A/a: Matt water based paints for internal walls and ceilings.

Legal limit of VOCValore : 30 g/l.

Maximum level of VOC in this product : 2.65 g/l

The advice and information given above are based on our experience and are of an informative nature and do not bind us to any responsibility. The application of the product takes place without our direct control, the user therefore takes all responsibility for any consequence of use. Our technical assistance team is available for any further information that might be necessary.

Technical data sheet PL/1150



FANCY ECO

Ecological paint for interiors. Breathable with low VOC content.



The advice and information given above are based on our experience and are of an informative nature and do not bind us to any responsibility. The application of the product takes place without our direct control, the user therefore takes all responsibility for any consequence of use. Our technical assistance team is available for any further information that might be necessary.